

THE RATIONALIZATION OF TODAY'S OFFICE



camera microfilm
simplex

3400

 **buic**[®]



camera microfilm simplex

3400

The Buic 3400 is a compact camera designed for the specific requirements of those firms where a single camera is shared by different departments. This camera is extremely versatile, economical and competitive.

THE INTERCHANGEABLE MAGAZINE ▶

The interchangeable Buic magazine enables to use just one microfilm camera for different uses and by several users. The insertion of the film is guided by the track path printed inside the magazine. At any moment it is possible to take out or replace the exposed films. This operation can be carried out in day light conditions.



FEEDER ▶

The automatic feeding device feeds about 3,000 documents of same thickness per hour. It is also possible to adjust the feeder to various paper thicknesses to avoid double document feeds.



Each frame can be coded with a three-level Blip corresponding to a three-level filing system.

Example: cabinet, shelf, folder.



Automatic frame indexing for fast retrieval in CAR systems.

The 3400 camera complies to international security regulations.

TECHNICAL DATA

| | |
|--------------------|---|
| Max. feeding width | cm. 33,5 |
| Reduction factor | 25 X (approx. 2500 DIN A4 documents per film) |
| Film | 16 mm. (30-60 mt. spools) |
| Lighting | 14 lamps, 24 Volts-21W |
| Frame counter | Resettable |
| Footage counter | Luminous LED indicator |
| Film transport | Automatic film advance at beginning and end of film, manual space button for intermediate spacing |
| Dimensions | 25 cm. high, 52 cm. deep, 42 cm. wide |
| • Film transport | Electronical checking with self-diagnosis on following operations: |
| • Film end | Automatic film advance lamp |
| • Magazine | Film finished |
| • Shutter | Magazine-missing/magazine badly inserted |
| • Lamps | Shutter not working |
| • Voltage | Camera stops automatically if a lamp burns out |
| • Weight | 220V 50Hz 2,5 Amp. Upon request 115V 60Hz 180W |
| | 28 Kg. |

OPTIONALS

- Feeder
- Interchangeable magazine
- Automatic exposure meter
- Three-level Blip - Frame sequential index

FEEDER SPECIFICATIONS

| | |
|----------------------------------|---------------------------------------|
| Max. feeding width | cm. 30 |
| Feeding speed | Approx. up to 3,000 A4 documents/h. |
| Sensibility of thickness control | Approx. up to 1 mm. |
| Dimensions | 15 cm. high, 29 cm. deep, 38 cm. wide |
| Weight | 9 Kg. |
| Voltage | 220/240V, 50Hz, 0,66 Amp. |

Specifications subject to change without notice.

buic

SYSTEMS

Buic Systems A.G. 6830 Chiasso Switzerland - Corso San Gottardo 35
Phone 0041/91/6900445 - Fax 0041/91/6900445

Distributed by:



